



REV.	DESCRIPTION	DRWN	CHKD	APPD	DATE
-	-	-	-	-	-

OUTER METAL

2ND LAYER OF 2" EPS FOAM

1/2" SILFLEX(TM)

1ST LAYER OF 2" EPS FOAM

OUTER METAL

PRE-CUT LIFTING EYES FOR SLINGS OR LIFTING CHAINS

HIGH STRENGTH HEAVY HINGE

FOLDING LEGS CAN BE LOCKED OUT FOR STABILITY

LEVELING CASTER

FOLDING LEGS CAN BE LOCKED IN FOR STORAGE

RADIATION BARRIER PANEL CAN BE USED TO ISOLATE POSSIBLE HOT SPOTS
BARRIER DIMENSIONS: 46" X 80"
OTHER HEIGHTS AVAILABLE

MECHANICAL LOCK FOR FOLDING LEGS (CAN BE LOCKED IN SEVERAL POSITIONS TO AVOID OBSTRUCTIONS)

SAFE ZONE

RADIATION BARRIER PANEL CAN BE USED TO ISOLATE POSSIBLE HOT SPOTS

ITEM No.	PART NUMBER	REQD PER ASSY	DESCRIPTION
BILL OF MATERIAL			
RADIATION BARRIER PANEL TYPICAL PANEL CONCEPTUAL RENDERINGS			
Scale: NTS	Job No.:	Size: D	Drawing Number: GA-100
Date:	Chkd:	Drwn: FRD/RC	Appd:
Sht: 1		Rev: 0	
Of: 2			

This drawing is CONFIDENTIAL but it may be disclosed or reviewed with other parties who have a reasonable need to know this information solely for the purpose of implementing this work for the owner. Under no circumstances may this be disclosed to the public or those not involved with the implementation of the project.

Proprietary Data
This plan or drawing is proprietary to Performance Contracting Incorporated and its or any copies thereof shall be retained open request. It is not to be copied, reproduced or exhibited to outside parties, but is to be used only with reference to contracts or proposals of this corporation. Having disclosed herein not publicly disclose may be used without written permission.

Ref. Dwg:

THIRD ANGLE PROJECTION

Unless otherwise noted tolerances are:
± 3mm for metric
± 1/8" for fractions
± 0.0025" for decimals
± 2' for angles

Customer's Purchase Order:

